

StrapPack®

Automatic Machine with Stainless Steel Body

The RQ-8SUS boasts all of the advanced features of the RQ-8 such as strap self-loading, refeed and loop ejection, but adds an attractive and practical stainless steel body.

- The fully enclosed stainless steel cabinet protects the components from water and wash-down spray. The bottom of the cabinet is reinforced to provide extra protection where moisture exposure is greatest. The dispenser can be raised to keep the strap dry.
- The RQ-8SUS can be built in most of the configurations available in the RQ-8 series. It brings the speed and performance of the RQ-8 into the poultry and meat processing industry.



■ Specifications of Standard Arch Size (650 mm wide x 500 mm high or 25" wide x 20" high)

Dimension	Width	1452 mm	57 -1/8 in.
	Height	1503 mm	59 - 1/8 in.
	Depth	609 mm	24 in.
	Weight	175 kg.	388 lbs.
Package Size	Min.	W 80 X H 30 mm	W 3-1/4 X H 4 in.
	Max. Weight	30 kg	66 lbs.
Joint / Strap/ Coil		heat seal / polypropylene ID 200 X OD 450 X W 200 mm	heat seal / polypropylene ID 8 X OD 18 X W 8 in.
Strap Width		5, 6, 9, 12, (15.5) mm	5mm, 1/4, 3/8, 1/2, (5/8) in.
Strap Tension		Max. 784N (80 kgf)	Max. 178 lbs.
Power Supply		100-120, 200-240 V 1 Phase 50 / 60 Hz 0.65 KVA	

RQ-8SUS